



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>H04N 7/24, 5/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/20049</b>  <b>(43) International Publication Date:</b> 22 April 1999 (22.04.99)
<b>(21) International Application Number:</b> PCT/US98/21556  <b>(22) International Filing Date:</b> 13 October 1998 (13.10.98)  <b>(30) Priority Data:</b> 60/061,897                      14 October 1997 (14.10.97)                      US  <b>(71) Applicant (for all designated States except US):</b> THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290-1024 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> EBLING, Mark, Jacob [US/US]; 6709 Stearns Hill Drive, Indianapolis, IN 46237 (US). HEREDIA, Edwin, Arturo [BO/US]; Apartment 4015, 8274 Lakeshore Circle, Indianapolis, IN 46250 (US). NIRANJAN, Sithampara [LK/US]; 613 Canoe Court, Redwood City, CA 94065 (US). TENG, Chia-Yuan [-/US]; Apartment #119, 11825 Caminito Ronaldo, San Diego, CA 92128 (US). OZKAN, Mehmet, Kemal [TR/TR]; Savasci Sokak Bozokatt 19/1, Avcilar, 34840 Istanbul (TR). SAEGER, Timothy, William [US/US]; 1203 Angelic Court, Carmel, IN 46032 (US).		<b>(74) Agents:</b> TRIPOLI, Joseph, S. et al.; GE & RCA Licensing Management Operation, Inc., P.O. Box 5312, Princeton, NJ 08540 (US).  <b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>With amended claims.</i>

**(54) Title:** SYSTEM FOR FORMATTING AND PROCESSING MULTIMEDIA PROGRAM DATA AND PROGRAM GUIDE INFORMATION

SYNTAX	BITS	FORMAT
multimedia object descriptor() {		
descriptor_tag	8	0x5F
descriptor_length	8	uimsbf
605   object_type	8	uimsbf
if (object_type = 0xFF) {		
extended_object_type	16	uimsbf
}		
610   address_descriptor		
object_format	8	uimsbf
object_version_number	7	uimsbf
display_mode	1	0/1
object_start_time	40	uimsbf
object_duration_format	2	uimsbf
object_duration	14	uimsbf
object_frame_size	32	uimsbf
}		

**(57) Abstract**

A program specific information data structure facilitates communication of program content and program guide data with attached multimedia objects including audio, video, animation, still image, Internet, Email, text and other types of data. The data structure supports uni-directional communication applications, e.g. passive viewing, and bi-directional communication applications, e.g. interactive type functions. A decoder (100) processes packetized program data and program specific information containing ancillary description information including multimedia object type, location and other descriptive indicators. These indicators are used in acquiring (22, 60), and decoding (30, 37, 60) multimedia objects derived from different sources for presentation (45, 50) in composite video images representing video program content or program guides, for example. Additional ancillary location and acquisition description information enables acquisition of supplementary program specific information elements and program content data.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## System for Formatting and Processing Multimedia Program Data and Program Guide Information

### *Field of the Invention*

5

This invention is related to the field of digital signal processing, and more particularly to the acquisition, formation and processing of Multimedia program guide and program content Information.

10

### *Background of the Invention*

Home entertainment systems which combine Personal Computer and television functions (PC/TV systems), are increasingly becoming, generic, User interactive, multiple source and multiple destination communication devices. Such multimedia systems are required to communicate in different data formats between multiple locations for a variety of applications in response to User requests. For example, a PC/TV system may receive data from satellite or  
20 terrestrial sources comprising High Definition Television (HDTV) broadcasts, Multi-point Microwave Distribution System (MMDS) broadcasts and Digital Video Broadcasts (DVB). A PC/TV system may also receive and transmit data via telephone (e.g. the Internet) and coaxial lines (e.g. cable TV) and from both remote and local sources  
25 such as Digital Video Disk (DVD), CDROM, VHS and Digital VHS (DVHS™) type players, PCs, and many other types of sources.

Forming and processing program guide data containing program content from numerous sources for multimedia applications presents a number of problems for such a generic PC/TV  
30 entertainment system. For example, such a system may be required

to process multimedia content including audio clips, video clips, animation, still images, text and other types of data encoded in different data formats. Specifically, difficulties arise in structuring program content and program guide data to facilitate the acquisition and decoding of multimedia content of different data format and from different sources. These problems and derivative problems are addressed by a system according to the present invention.

### *Summary of the Invention*

10

A program specific information data structure facilitates communication of program content and program guide information with attached multimedia data including audio, video, animation, still image, Internet, Email, text and other types of data. The data structure supports uni-directional communication applications e.g. passive viewing and bi-directional communication applications e.g. interactive type functions. A decoder processes packetized program data containing ancillary description information including multimedia object type, location and other descriptive indicators. These indicators are used in acquiring, and decoding multimedia objects derived from different sources for presentation in composite video images representing video program content or program guides, for example. Additional ancillary location and acquisition description information enables acquisition of supplementary program specific information elements and program content data.

In the drawing:

Figure 1 shows an exemplary hierarchical program guide data structure for conveying multimedia object data, according to the invention.

Figure 2 shows an exemplary program guide display containing multimedia objects, according to the invention.

Figures 3-6 show, respectively, a Master Guide Table (MGT), Additional Guide Data Table (AGDT), Channel Information Table (CIT) and a Multimedia Object Descriptor (MOD) Table used in the hierarchical data structure of Figure 1, according to the invention.

Figure 7 describes the elements of the Multimedia Object Descriptor (MOD) Table of Figure 6, according to the invention.

Figures 8 and 9 respectively list and describe other descriptors that may be incorporated in program specific information to facilitate multimedia data acquisition and decoding, according to the invention.

Figures 10, 11 and 12 list acquisition descriptors for use in acquiring multimedia objects from exemplary locations including Internet locations, digital storage media datastream locations and MPEG PSI stream locations respectively, according to the invention.

Figure 13 shows an acquisition descriptor for acquiring program specific information and multimedia objects from different sources including MPEG PSI streams and Internet locations, for example, according to the invention.

Figure 14 shows an exemplary list of the types of tables that may use the acquisition descriptor of Figure 13, according to the invention.

Figures 15 and 16 respectively show location descriptors for use in identifying multimedia content data from different sources including an MPEG compatible source and a Digital Satellite System (DSS) source, according to the invention.

Figure 17 shows a flowchart of a method for forming program specific information to convey multimedia objects, according to the invention.

Figure 18 shows a home entertainment decoder system for forming and decoding multimedia program data and program guide information, according to the invention.

#### *Detailed Description of the Drawings*

Program specific information (PSI) includes program guide data and information for use in identifying and assembling individual data packets to recover the content of selected program channels. Program specific information and associated program content is advantageously structured to support communication of multimedia objects including audio clips, video clips, animation, still images, Internet data, Email messages, text and other types of data. Multimedia objects are data entities that may be viewed as independent units and are associated with images within individual programs or with program guide components. The multimedia objects are incorporated into composite video images representing a program guide or a video program, for example. The data structure supports uni-directional communication applications e.g. passive viewing and bi-directional communication applications e.g. interactive type functions and also supports storage applications.

The program specific information and associated program content may be delivered by different service providers via the Internet, or via terrestrial, satellite or cable broadcast on a subscription or other pay per view basis. The data structure facilitates acquisition and decoding of multimedia objects encoded in different data formats and which are communicated in different communication protocols from both local and remote sources. An exemplary decoder, receives program content from satellite, cable and terrestrial sources including via telephone line from Internet sources, for example.

Hereinafter, data referred to as being MPEG compatible conforms to the MPEG2 (Moving Pictures Expert Group) image encoding standard, termed the "MPEG standard". This standard is comprised of a system encoding section (ISO/IEC 13818-1, 10th June 1994) and a video encoding section (ISO/IEC 13818-2, 20th January 1995).

Data structure elements according to the invention principles may be conveyed in MPEG compatible format (per section 2.4.4 of the MPEG systems standard) or may be conveyed in a format compatible with the *Program and System Information Protocol for Terrestrial Broadcast and Cable*, published by the Advanced Television Systems Committee (ATSC), 10 November 1997, hereinafter referred to as the PSIP standard or other ATSC standards. Further, the data structure elements may be formed in accordance with proprietary or custom requirements of a particular system.

The principles of the invention may be applied to terrestrial, cable, satellite, Internet or computer network broadcast systems in which the coding type or modulation format may be varied. Such systems may include, for example, non-MPEG compatible systems, involving other types of encoded datastreams and other

methods of conveying program specific information. Further, although the disclosed system is described as processing broadcast programs, this is exemplary only. The term 'program' is used to represent any form of packetized data such as audio data, telephone messages, computer programs, Internet data or other communications, for example.

Figure 1 shows an overview of an exemplary hierarchical program specific information data structure for conveying multimedia object data, according to the invention. The structure comprises multiple hierarchically arranged and inter-linked tables and multimedia objects (Object 1 and Object 2). The tables consist of arrays of data and parameters which are used to enumerate and describe collections or sequences of TV channels, TV programs, channel parameters, program parameters, associated multimedia objects and object parameters, etc. The exemplary hierarchical table arrangement of Figure 1 includes a Master Guide Table (MGT) 205, Additional Guide Data Table (AGDT) 210, Channel Information Tables (CIT-1, CIT-2, CIT-3), Event Information Tables (EIT-1, EIT-2), Network Information Table NIT 220, and optional tables such as Extended Channel Information Tables (ECIT-1, ECIT-2, ECIT-3), and Extended Event Information Tables (EEIT-1, EEIT-2).

The MGT contains information for use in acquiring program specific information conveyed in other tables and specifically, in this exemplary embodiment, provides information for use in acquiring the AGDT. The AGDT contains information for determining the structure and table partitioning of the program specific information. The CIT contains information for tuning and navigation to receive a User selected program channel. The EIT contains descriptive lists of programs (events) receivable on the channels listed in the CIT. Either a CIT, EIT or other table may be used



to convey information enabling a user to select and tune to a particular program. A CIT is typically used to convey parameters for acquiring audiovisual program content data that remains constant over several events (TV programs). An EIT is typically used to convey parameters of audiovisual program content data that remain constant for an event (individual TV program). The NIT contains parameter lists for the entire broadcast network (terrestrial, satellite, cable, etc.). The ECIT and EEIT are extension tables accommodating additional CIT and EIT information. Additional program specific information describing and supplementing items within the hierarchical tables is conveyed within descriptor information elements.

This data structure advantageously enables multimedia objects and table information located at a plurality of different remote and local sources to be acquired at a decoder and assembled to produce an individual program and program guide for display to a user. The data structure incorporates address and protocol information for identifying and acquiring tables and objects from a variety of sources. The data structure enables objects to be positioned anywhere in a program guide and to be associated with individual program specific information table elements. A decoder uses the address and protocol information and other parameters in the data structure to acquire and format a composite program guide and programs from tables and objects derived from a plurality of distributed sources. As such the data structure offers flexibility and adaptability advantages and provides a comprehensive mechanism for conveying a multiplicity of distributed multimedia objects in a manner that facilitates efficient decoding and reproduction of composite video images and audio segments. Other methods of partitioning program specific information may be used in conveying multimedia objects and may achieve similar flexibility, adaptability

and efficiency advantages by employing the table structuring, and multimedia object definition and acquisition information, according to the invention principles. The elements of the data structure presented in Figures 1-16 are considered to be optional and may be used or  
5 omitted based on the requirements of a particular system.

Figure 2 shows an exemplary program guide display that may be produced by a decoder from the program specific information structure, according to the invention. The program guide contains multimedia objects and provides a user interface that supports Email,  
10 telephone, fax, Internet browsing, storage, home shopping, home banking (420-433) and other functions. Multimedia objects such as video clips, Internet web page data or still images may be displayed in area 435 in response to user selection of a preview icon (e.g. 447, 449) or a web page icon (e.g. 443). Data and text such as Email  
15 messages, sports results or stock quotes etc. are displayed in area 439 in response to user selection of a results icon (e.g. 445) or in response to user selection of functions 420-433. Advertisements and animation may similarly be displayed in area 437.

Figures 3-6 show, respectively, a Master Guide Table (MGT), Additional Guide Data Table (AGDT), Channel Information Table (CIT) and a Multimedia Object Descriptor (MOD) Table used in the hierarchical data structure of Figure 1, according to the invention. Figure 3 shows an MGT providing pointer information specifically for use in acquiring the AGDT.  
20

Figures 4 and 5 comprise an exemplary AGDT for conveying information for acquiring and assembling the other tables and components of the program specific information. The AGDT describes the structure and locations of the data partitions that are used in conveying the program specific information. A decoder uses  
25 the control information in the AGDT in assembling the program  
30

specific information and in creating a program guide for display. Although the AGDT is shown as separate Figures for clarity (Figures 4 and 5), the AGDT actually comprises a single table in which the syntax of Figure 5 occupies the program\_guide\_map element 415 of Figure 4.

5           The AGDT syntax of Figure 4 indicates a first level of program specific information partitioning and provides:

- An overall description for the entire guide (e.g. descriptor 405).
- 10   • A definition of partitioning of network parameters (for cable, terrestrial, digital broadcast satellite, Internet, type networks, for example).

One or more pointer descriptors may be inserted at line 15 405 of Figure 4 to indicate the location of the entire program specific information and/or its table components. Similarly, if network-based partitioning is used, the location of network information tables can be indicated by inserting proper pointer descriptors in line 410. Table pointer descriptors comprise acquisition descriptors as exemplified by 20 the syntax structure of Figure 13 which is discussed later. Further, multimedia object descriptors (MODs) may be inserted in the AGDT at line 405, to associate multimedia objects external to the program specific information with the program specific information (or program guide) as a whole, or may be inserted at line 410, to 25 associate external objects with particular network parameter arrangements. An external multimedia object is an object that is provided by a remote or local source and is not conveyed within the program specific information itself. For example, an advertisement sponsoring a program guide conveyed within the program specific

information may be linked to the guide for display by using one or more MODs in line 405.

In order to support such a function, an MOD advantageously incorporates indications of:

5

- the type of object being described (e.g. Email MIME format, Internet HTML, still image JPEG format, video clip MPEG2 format etc.)
- the location of the object (PSI bit stream, FTP site, WWW site, DSM-CC stream, etc.)

10

An exemplary MOD syntax structure incorporating an object type indicators and address location pointer is presented in Figure 6 and is discussed in more detail later.

15

The AGDT syntax of Figure 5 indicates a second level of program specific information partitioning that may be used to partition program specific information by time segment and channel characteristic or group. The program specific information time segment partitions are defined by a syntax element loop beginning at line 510. Pointer (location) descriptors for locating tables or objects may be inserted at line 515. Further, one or more additional pointer descriptors may be inserted at line 505 of Figure 5 to indicate the location of multimedia objects and tables that are valid for all the time segment partitions. The program specific information channel characteristic partitions are defined by a syntax element loop beginning at line 520 and pointer (location) descriptors for locating tables or objects for particular channel groups may be inserted at line 525. Further, multimedia object descriptors (MODs) may also be inserted in the AGDT descriptor sections of Figure 5 to associate

20

25

multimedia objects external to the program specific information with particular time segments or channel groups. As previously stated, AGDT elements may be viewed as optional in tailoring the data structure for particular system requirements. For example, the  
5 previously described syntax enabling partitioning of the program specific information into different channel groups may be omitted in a particular application.

Figure 6 shows an exemplary multimedia object descriptor (MOD) for use in defining multimedia objects to be incorporated in  
10 displayed program content or in a displayed program guide, for example. The MOD syntax shown in Figure 6 may be incorporated in a plurality of locations throughout the program specific information structure in order to associate multimedia objects with individual image or data components of a program guide or program content.  
15 The MOD identifies objects associated with program specific information components using the object type field (line 605) and identifies the location of the object to enable its acquisition using the address descriptor field (line 610). The key elements of the MOD shown in Figure 6 may be advantageously used for conveying  
20 multimedia object acquisition information in a wide variety of data transport structures that may be used to deliver program content or program guide information. Such transport structures, for example, may include MPEG-PSI, Internet TCP/IP (Transport Control Protocol/Internet Protocol), DSS (Digital Satellite System), ATM  
25 (Asynchronous Transfer Mode) etc.

Figure 7 describes the elements of the Multimedia Object Descriptor (MOD) of Figure 6.

Figure 8 (items 805-850) and Figure 9 respectively list and describe other descriptor types that may be incorporated in

program guide information to facilitate multimedia object acquisition and decoding, according to the invention.

Figures 10, 11 and 12 list address descriptors for use in acquiring multimedia objects from exemplary locations including Internet locations, digital storage media datastream locations and MPEG PSI stream locations respectively. Any or all of these address descriptors (or alternatively defined address descriptors) may be included within the MOD at line 610 of Figure 6. The descriptor of Figure 10 identifies web-based locations from which multimedia objects are acquired using an Internet URL address 905. The descriptor of Figure 11 identifies objects in a DSM-CC (Digital Storage Medium-Command and Control) stream from which multimedia objects are acquired using a DSM-CC\_association\_tag 910 as a link with a particular object in a DSM-CC carousel. The descriptor of Figure 12 identifies locations of objects in an MPEG-2 PSI stream. Within the descriptor of Figure 12, item 915 identifies a particular network (e.g. satellite, cable, or terrestrial), item 920 identifies a particular network transport stream (transport stream id), item 925 identifies packets within a particular stream using a Packet Identifier (PID) and item 930 identifies particular table associations of the packets with table identifiers (table\_id and table\_id\_extension). Similar descriptors may be derived for other media according to the invention principles exemplified in Figures 10-12.

Figure 13 shows an acquisition descriptor for defining table locations for acquiring program specific information and multimedia objects from different sources including MPEG PSI streams and Internet locations, for example. This descriptor may be used throughout the program specific information structure to identify table locations. The acquisition descriptor of Figure 13 may be used at line 405 of the AGDT of Figure 4 to identify tables that are

not associated with particular program specific information parameters. Alternatively, the acquisition descriptor of Figure 13, may be used at line 410 of the AGDT of Figure 4 to identify tables associated with particular networks. Further, the acquisition  
5 descriptor of Figure 13, may be used in other portions of the AGDT, such as within time-based partitions of particular channel groups. As an example, the descriptor of Figure 13 incorporates elements for acquiring program specific information tables from two separate sources. Specifically,

10

(1) items 960 and 965 enable data acquisition from MPEG-2 PSI streams, and

(2) item 970 enables data acquisition from an Internet address such as from an FTP or HTTP compatible source.

15

The Figure 13 descriptor structure is flexible and readily accommodates additional different addressing methods through the addition of extra "else if" statements to the descriptor. In adapting or expanding the Figure 13 data structure to encompass additional  
20 addressing elements, item 955 is used to identify the particular table being defined in the Figure 13 execution loop and item 950 determines the number of tables for which acquisition locations are defined.

Figure 14 shows an exemplary list of the types of tables  
25 that may use the acquisition descriptor of Figure 13 and that may be incorporated into the program specific information structure, according to invention principles. In using the acquisition descriptor of Figure 13 to acquire the tables listed in Figure 14, the element identifier values of the desired table listed within Figure 14 are  
30 inserted in the element identifier field at line 955 of the acquisition

descriptor of Figure 13. Other tables may also be acquired, partitioned and incorporated in the program specific information structure as desired using data structuring principles described.

Figures 15 and 16 show examples of a location descriptor for use in acquiring multimedia audiovisual content data from different sources using different communication protocols and data formats (as distinct from the descriptor of Figure 14 used in acquiring program specific information from different sources). The location descriptor exemplified in Figures 15 and 16 may be incorporated into program specific information tables such as into a Channel Information Table (CIT) or into an Event Information Table (EIT) and is used to identify audiovisual content data within input datastreams. Specifically, Figure 15 shows an example of a location descriptor for use in acquiring audiovisual data from an MPEG compatible source and Figure 16 shows an example of the location descriptor data structure for use in acquiring audiovisual data from a Digital Satellite System (DSS) source. A plurality of location descriptors may be included in program specific information in order to acquire audiovisual content data from,

- (a) multiple different sources and types of media (e.g. MPEG, Internet, cable sources), and
- (b) from different addresses associated with a particular source or media type (e.g. from different Internet addresses or cable TV channels).

In the location descriptor example of Figure 15 MPEG compatible audiovisual data is identified by PID value. The location descriptor of Figure 15 includes two methods of data acquisition based on PID value. The two methods are referred to as an implicit method and an explicit method respectively. Selection between the two methods is determined by an input implicit flag indicator 985.



In the explicit method, the PIDs, e.g. PID 990, are individually listed within a loop beginning at line 987. In the implicit method a base PID 993 is defined and other PIDs are derived from the base PID in accordance with a predetermined PID definition e.g. as  
5 a function of program channel number and stream type. Such an implicit method is known and described for example in an ATSC standard. The stream type associated with a particular PID is defined by element SType[i] in Figures 15 and 16.

In the location descriptor example of Figure 16  
10 audiovisual data from a Digital Satellite System (DSS) source is identified by SCID (Service Component Identifier) value. The location descriptor of Figure 16 includes two methods of data acquisition (an implicit and explicit method) based on SCID value, in similar fashion to the MPEG example of Figure 15. Selection between the two methods  
15 is determined by an input implicit flag indicator 353.

In the explicit method, the SCIDs, e.g. SCID 355 or 357, are individually listed within a "for" loop beginning following line 353. In the implicit method a base SCID 360 or 363 is defined and other SCIDs are derived from the base SCID in accordance with a predetermined  
20 SCID definition, as previously mentioned. In the DSS case, however, the SCID values may have two different sizes. Consequently, within the DSS location descriptor structure an input selection parameter (Z\_bit) is used in selecting between SCID values. Specifically, in Figure 16 selection parameter (Z\_bit) is used in selecting between SCIDs 355  
25 and 357 in the explicit case and in selecting between SCIDs 360 and 363 in the implicit case.

The descriptor tag 980 of Figure 15 and the descriptor tag 350 of Figure 16 are used within a decoder for identifying a descriptor type and for automatically differentiating between  
30 descriptors. In a decoder, it is determined whether a particular

desired channel (and associated program) is transmitted from a particular source (e.g. satellite, terrestrial, cable, or Internet source) and thereupon the corresponding satellite, terrestrial, cable, or Internet location descriptor is selected for use. A variety of other  
5 location descriptors may be defined in similar fashion to those exemplified in Figures 15 and 16. Such other descriptors may be used to acquire digital audiovisual services from sources including, for example, streamed audio and video over the Internet, ATM networks, etc.

10 Figure 17 shows a flowchart of a method for forming program specific information to convey multimedia objects, according to the invention. The method of Figure 17 generates program specific information including MGT, AGDT, CIT, ECIT, EIT, EEIT, NIT and ETT  
15 data and descriptors containing the advantageous features previously described. The method may be employed at an encoder for broadcasting video data or the method may be employed within a decoder unit.

Following the start at step 250 of Figure 17, in step 253, a method based on the previously described data structuring principles  
20 is selected for partitioning program specific information. The program specific information is partitioned in accordance with network types, time segments, channel groups, transport stream channel groupings and the programs (events) being transmitted on particular channels. In step 255, the locations of table partitions and the tables and sub-  
25 tables (extended tables) required to accommodate the partitioned program specific information are identified and descriptors for identifying and acquiring the tables and associated multimedia objects are formed. In step 257 an AGDT (or another type of control table) is generated to include those formed acquisition and  
30 multimedia object descriptors generated in step 257 that apply to the

AGDT level of program specific information structure. In addition, an MGT is generated in step 257 containing information for use in acquiring program specific information conveyed in other tables and specifically for use in acquiring an AGDT.

5           In step 260 individual CIT, ECIT, EIT, EEIT, NIT and ETT etc. tables are formed complying with the partitioned structure. The individual tables incorporate acquisition descriptors, multimedia object descriptors (MODs) and location descriptors derived according to the previously described invention principles. A CIT is formed  
10 containing sub-channel and program identification information enabling acquisition of available broadcast programs and channels. containing packet identifiers for identifying individual packetized datastreams that constitute individual programs to be transmitted on particular channels. The generated CIT also incorporates items linked  
15 to listed program channels including a program number, a PCR (Program Clock Reference) identifier, a language code indicator, and a stream type identifier, for example.

          Further, in step 260, an EIT is generated containing program guide information including descriptive lists of programs  
20 (events) receivable on the channels listed in the CIT. Also in step 260, an NIT is created and an ETT is generated containing text messages describing programs, for example. Further, extension tables are formed as necessary to accommodate additional partitioned program specific information.

25           In step 263, the tables formed in step 260, together with associated multimedia objects, are formatted to be compatible with a desired data format and protocol. Such data formats and protocols include, for example, MPEG2 compatible Program Specific Information, MPEG2 DSM-CC, DSS, and an Internet compatible file  
30 transfer format. In step 265, the resulting formatted tables and

multimedia objects are incorporated into a datastream in their designated locations for terrestrial transmission. The AGDT is incorporated into the datastream in step 267.

5 In step 270, the program specific information produced in step 267, together with video and audio program representative components (and other data) for multiple channels, is multiplexed and formatted into a transport stream for output. In step 270, the output transport stream is further processed to be suitable for terrestrial transmission to another device such as a receiver, video server, or  
10 storage device for recording on a storage medium, for example. The processes performed in step 270 include known encoding functions such as data compression Reed-Solomon encoding, interleaving, scrambling, trellis encoding, and carrier modulation. The process is complete and terminates at step 275. In the process of Figure 17,  
15 multiple CIT, EIT, ETT and associated extension tables may be formed and incorporated in the program specific information in order to accommodate expanded numbers of channels. Further, in other embodiments the tables may be similarly processed for satellite, cable or Internet transmission, for example.

20 Figure 18 is a block diagram of a digital video receiving system for demodulating and decoding broadcast (terrestrial, satellite, cable, or Internet) signals. In terrestrial mode, a carrier modulated with signals carrying program representative MPEG compatible audio, video and associated data received by antenna 10, is converted to  
25 digital form and processed by input processor 13. Processor 13 includes radio frequency (RF) tuner and intermediate frequency (IF) mixer and amplification stages for down-converting the input signal to a lower frequency band suitable for further processing. In this exemplary system, the terrestrial input signal received by antenna 10  
30 contains 33 Physical Transmission Channels (PTCs 0-32). Each

Physical Transmission Channel (PTC) is allocated a 6 MHz bandwidth and contains, for example, up to 6 sub-channels.

It is assumed for exemplary purposes that a video receiver user selects a sub-channel (SC) for viewing using remote control unit 70. Processor 60 uses the selection information provided from remote control unit 70 via interface 65 to appropriately configure the elements of decoder 100 to receive the PTC corresponding to the selected sub-channel SC. Following down conversion, the output signal from unit 13 for the selected PTC has a bandwidth of 6 MHz and a center frequency in the range of 119-405 MHz. In the following discussion, an RF channel or Physical Transmission Channel (PTC) refers to an allocated broadcaster transmission channel band which encompasses one or more sub-channels (also termed virtual or logical channels).

Processor 60 configures the radio frequency (RF) tuner and intermediate frequency (IF) mixer and amplification stages of unit 13 to receive the selected PTC using bi-directional control and signal bus C. The down-converted frequency output for the selected PTC is demodulated by unit 15. The primary functions of demodulator 15 are recovery and tracking of the carrier frequency, recovery of the transmitted data clock frequency, and recovery of the video data itself. Unit 15 also recovers sampling and synchronization clocks that correspond to transmitter clocks and are used for timing the operation of processor 13, demodulator 15 and decoder 17. The recovered output from unit 15 is provided to decoder 17.

The output from demodulator 15 is mapped into byte length data segments, deinterleaved and Reed-Solomon error corrected according to known principles by unit 17. In addition, unit 17 provides a Forward Error Correction (FEC) validity or lock indication to processor 60. Reed-Solomon error correction is a known

type of Forward Error Correction. The FEC lock indication signals that the Reed-Solomon error correction is synchronized to the data being corrected and is providing a valid output. It is to be noted that the demodulator and decoder functions implemented by units 13, 15 and 17 are individually known and generally described, for example, in the reference text *Digital Communication*, Lee and Messerschmidt (Kluwer Academic Press, Boston, MA, USA, 1988).

In other modes satellite, cable and Internet data is received on input lines 11, 14 and 18 and processed by interface access modules 74, 78 and 72 respectively. Interface modules 74, 78 and 72 incorporate interface functions for satellite, cable and Internet format data respectively. Such functions are known and detailed in applicable standards and other documents. These interface functions correspond to those performed by units 13, 15 and 17 in terrestrial mode. Further, in similar fashion to terrestrial mode, processor 60 configures units 74, 78, 72 and decoder 100 to receive satellite, cable or Internet data using bi-directional control and signal bus C. Decoder 100 processes the data conditioned by units 74, 78 or 72 in these other modes using similar functions as described for terrestrial mode.

The corrected output data from unit 17 is processed by MPEG compatible transport processor and demultiplexer 22. The individual packets that comprise either particular program channel content, or program specific information, are identified by their Packet Identifiers (PIDs). Processor 22 separates data according to type based on an analysis of Packet Identifiers (PIDs) contained within packet header information and provides synchronization and error indication information used in subsequent video, audio and data decompression.

The corrected output data provided to processor 22 is in the form of a transport datastream containing program channel

content and program specific information for many programs distributed through several sub-channels. The program specific information in this exemplary description describes sub-channels present in a transport stream of a particular PTC. However, in another embodiment the program specific information may also describe sub-channels located in other PTCs and conveyed in different transport streams. Groups of these sub-channels may be associated in that their source is a particular broadcaster or they occupy the transmission bandwidth previously allocated to an analog NTSC compatible broadcast channel. Further, individual packets that comprise a selected program channel in the transport stream are identified and assembled by processor 60 operating in conjunction with processor 22 using PIDs contained in the program specific information.

The program specific information is acquired and assembled by processor 60, operating in conjunction with unit 22, from the datastream input from unit 17. Processor 60 determines from the FEC lock indication provided by unit 17 that valid data is being provided to transport processor 22. Thereupon, the program specific information MGT and AGDT tables are identified and assembled using predetermined PID values stored within processor 60 internal memory. Using Control signal C, processor 60 configures transport processor 22 to select the data packets comprising the remaining program specific information including the CIT, EIT, ETT and NIT data. The program specific information tables may be acquired from a plurality of sources using the acquisition descriptor information previously described in connection with Figures 13 and 14. The tables may be acquired by processor 60 initiating communication with different sources (e.g. satellite, cable, or Internet sources), in different data formats and transmission protocols via different transmission media such as via satellite feed 11, cable line

14 or phone line 18. The acquisition descriptor information, either alone or as supplemented by other program specific information, enables processor 60 to establish communication in different data formats and transmission protocols. This is achieved using interface  
5 units 72, 74 and 78 to establish either, uni-directional communication (e.g. for satellite communication), or bi-directional communication (e.g. for Internet communication).

Processor 22 matches the PIDs (or other data identifiers e.g. TCP/IP identifiers, SCIDs etc.) of incoming packets provided by  
10 unit 17 (or units 72, 74 and 78 for Internet, cable or satellite data sources) with PID values pre-loaded in control registers within unit 22 by processor 60. Further, processor 60 accesses, parses and assembles the program specific information packets captured by processor 22 and stores the program specific information within its  
15 internal memory. Further, in response to a channel SC selection command from remote unit 70 via interface 65, processor 60 derives tuning parameters including PTC carrier frequency, demodulation characteristics, and sub-channel PIDs, from the acquired program specific information including location, acquisition and MOD  
20 descriptors. Processor 60 uses this information in configuring units 13, 15, 17 and decoder 100 elements to acquire selected sub-channel (SC) program content.

The packetized decoded transport stream input to decoder 100 from unit 17 (or units 72, 74 or 78) contains video, audio and  
25 data representing TV programs, for example, and also contains sub-picture data. The sub-picture data contains picture elements associated with programs and channels selectable by a user for viewing including, multimedia objects, program guides, display commands, subtitling, selectable menu options or other items, for  
30 example. As such, the sub-picture data includes multimedia objects



acquired using MODs and an EIT containing descriptive lists of programs (events) receivable on the sub-channels listed in a CIT and also contains an ETT containing text messages describing programs and program sub-channels.

5           The video, audio, data and sub-picture data being transmitted on terrestrial sub-channel SC, together with associated data from satellite, cable or Internet sources from units 74, 78 and 72, is acquired by processor 60 operating in conjunction with unit 22. This is achieved using the collated program specific information  
10 including location and MOD descriptors. Processor 60 identifies the video, audio, data and sub-picture data using respective PIDs (or other identifiers) determined from the CIT and descriptors. Processor 60 also initiates communication with other data sources (e.g. cable, satellite or Internet sources) in order to acquire video, audio, data and  
15 sub-picture data from these sources. Processor 60 and unit 22 initiates the communication and identifies and captures the video, audio, data and sub-picture data from other sources using location descriptor information of the type previously described in connection with Figures 15 and 16. Similarly, processor 60 and unit 22 initiates  
20 communication and identifies and captures multimedia objects from other sources using MOD information of the type previously described in connection with Figures 6-12. The location descriptor and MOD information, either alone or as supplemented by other program specific information, enables processor 60 to establish communication  
25 in different data formats and transmission protocols. As previously explained, this is achieved using interface units 72, 74 and 78 to establish either, uni-directional communication (e.g. in the satellite communication mode), or bi-directional communication (e.g. in cable or Internet communication mode).

Processor 22, matches the PIDs (or other identifiers) of incoming packets provided by decoder 17 and interface units 72, 74 and 78 with identifier values of the video, audio and sub-picture data being transmitted on sub-channel SC and also being input via communication lines 11, 14 and 18. In this manner, processor 22 captures packets constituting the program transmitted on sub-channel SC and associated data and multimedia objects (e.g. advertisements, web page data, interactive icons etc.). Processor 22 forms these packets into MPEG compatible video, audio and sub-picture streams for output to video decoder 25, audio decoder 35 and sub-picture processor 30 respectively. The video and audio streams contain compressed video and audio data representing the selected sub-channel SC program content. The sub-picture data contains multimedia objects and EIT and ETT information associated with the sub-channel SC program content and program guide information.

Decoder 25 decodes and decompresses the MPEG compatible packetized video data from unit 22 and provides decompressed program representative pixel data to NTSC encoder 45 via multiplexer 40. Similarly, audio processor 35 decodes the packetized audio data from unit 22 and provides decoded and amplified audio data, synchronized with the associated decompressed video data, to device 55 for audio reproduction. Processor 30 decodes and decompresses sub-picture data including multimedia objects received from unit 22 to provide image representative multimedia object, text, caption and graphics data. In decoding multimedia objects, processor 30 applies a decoding function determined using the associated MOD information elements exemplified in Figures 6 and 7.

Processor 30 (Figure 18) assembles and formats the decoded and decompressed multimedia object, text, caption and

graphics data for output to On-Screen Display (OSD) and graphics generator 37. In formatting decoded multimedia objects, processor 30 (in conjunction with unit 37), under direction of unit 60, determines how, where, and when individual objects are to be displayed from  
5 MOD information (or equivalent elements) such as object\_format, display\_mode, object\_start\_time, object\_duration, object\_frame\_size as shown in Figures 6 and 7, for example. An individual object may also be linked to other program or program guide images by processor 30 using linkage and attribute descriptors, for example  
10 (items 825 and 840 of Figures 8 and 9). Alternatively, other descriptors and descriptor elements performing a similar linkage function may be employed. A multimedia object may also be linked with particular sub-channels, program images, scenes or program guide pages or web pages, for example, by incorporating MOD  
15 descriptor information into an EIT or CIT or other table. In this method, an object is directly linked to a program image (or sub-channel, scene or program guide or web page image) by association with descriptive elements of the program within the EIT or CIT.

Unit 37 of Figure 18 interprets and formats the  
20 multimedia objects and other data from unit 30 using the linkage and formatting information (as described in connection with processor 30 above) of Figures 6 and 8 as supplemented by CIT and EIT information and generates formatted pixel mapped text and graphics for presentation on unit 50 (Figure 18). The formatted pixel mapped  
25 text and graphics data may represent multimedia objects or a program guide or other type of menu or user interface for subsequent display on unit 50. Unit 37 also processes EIT, ETT and other information to generate pixel mapped data representing, subtitling, control and information menu displays including selectable menu  
30 options, and other items, for presentation on unit 50. The control and

information displays enable function selection and entry of device operating parameters for User operation of decoder 100.

The text and graphics produced by OSD generator 37 are generated in the form of overlay pixel map data under direction of processor 60. The overlay pixel map data from unit 37 is combined  
5 and synchronized with the decompressed pixel representative data from MPEG decoder 25 in encoder 45 via multiplexer 40 under direction of processor 60. Thereby multimedia objects such as advertisements, web page data, interactive icons etc. may be included  
10 in program content or program guides for display. Combined pixel map data representing a video program and associated multimedia objects together with associated sub-picture text message data is encoded by NTSC encoder 45 and output to device 50 for display.

In a storage mode of the system of Figure 18, the  
15 corrected output data from unit 17 is processed by decoder 100 to provide an MPEG compatible datastream for storage. In this mode, a program is selected for storage by a user via remote unit 70 and interface 65. Processor 22, in conjunction with processor 60 forms condensed program specific information including MGT, AGDT, CIT,  
20 EIT and ETT data and location, acquisition and multimedia object descriptors containing the advantageous features previously described. The condensed program specific information supports decoding of the program selected for storage but excludes unrelated information. Processor 60, in conjunction with processor 22 forms a  
25 composite MPEG compatible datastream containing packetized content data of the selected program and associated condensed program specific information. The composite datastream is output to storage interface 95.

Storage interface 95 buffers the composite datastream to  
30 reduce gaps and bit rate variation in the data. The resultant buffered

data is processed by storage device 90 to be suitable for storage on medium 105. Storage device 90 encodes the buffered datastream from interface 95 using known error encoding techniques such as channel coding, interleaving and Reed Solomon encoding to produce  
5 an encoded datastream suitable for storage. Unit 90 stores the resultant encoded datastream incorporating the condensed program specific information on medium 105.

The architecture of Figure 18 is not exclusive. Other architectures may be derived in accordance with the principles of the invention to accomplish the same objectives. Further, the functions of  
10 the elements of decoder 100 of Figure 18 and the process steps of Figure 17 may be implemented in whole or in part within the programmed instructions of a microprocessor. In addition, the principles of the invention apply to any form of MPEG or non-MPEG  
15 compatible electronic program guide. A datastream formed according to the invention principles may be used in a variety of applications including video server or PC type communication via telephone lines, for example. A program datastream with one or more components of video, audio and data formed to incorporate program specific  
20 information according to invention principles may be recorded on a storage medium and transmitted or re-broadcast to other servers, PCs or receivers.

## CLAIMS

1. Apparatus for decoding packetized program information from a first source to provide data content of a program, comprising:

5 means for identifying (22,60) ancillary information in said packetized program information, said ancillary information including information describing a multimedia image object associated with an image in said packetized program information, said multimedia object description information comprising,

10 (a) a location indicator (610) identifying a location of a multimedia object for use in acquiring said multimedia object, and

(b) a type indicator (605) identifying a multimedia object type for use in decoding said multimedia object; and

15 means for acquiring and decoding (22, 30, 60) said multimedia object using said multimedia object description information; and

means for formatting (30, 37, 60) said multimedia object for display.

20 2. Apparatus according to claim 1, wherein

said location indicator identifies a location of said multimedia object in one of (a) said packetized program information from said first source, and (b) information derived from a second source different to said first source.

25

3. Apparatus according to claim 2, wherein

said location indicator identifies a location of said multimedia object derived from said first source using one of (a) an MPEG compatible packet Identifier (PID), (b) an MPEG compatible  
30 Digital Storage Media code.

4. Apparatus according to claim 2, wherein  
said location indicator identifies a location of said  
multimedia object derived from said second source using one of (a) an  
Internet URL, (b) an Internet IP address, (c) an Email address, (d) a  
5 telephone/fax/videophone number.

5. Apparatus according to claim 4, wherein  
said means for acquiring said multimedia object includes  
establishing bi-directional communication with said second source  
10 using said location indicator, and said bi-directional communication  
path is different to the communication path between said decoding  
apparatus and said first source.

6. Apparatus according to claim 1, wherein  
15 said multimedia object type comprises at least one of, (a) a  
video segment or still image, (b) an audio segment, (c) text, (d) an  
Internet web page or Internet data, (e) an advertisement, (f) an icon  
for user selection of a service, (g) an animation segment, (h) an Email  
message, (i) a user prompting indicator, and (j) a broadcast channel  
20 identification icon.

7. Apparatus according to claim 1, wherein  
said multimedia object description information further  
includes at least one of, (a) an object start time, (b) an object duration,  
25 (c) an object display mode, (d) an object version number, (e) an object  
format, for use in decoding.

8. Apparatus according to claim 1, wherein  
said formatting means includes means for associating said  
multimedia object with one of (a) a video image, and (b) audio data,  
5 and

said formatting means forms a composite image for  
display combining said multimedia object and at least one of, (a) an  
electronic program guide, (b) a video program, and (c) an Internet  
web page image.

10

9. Apparatus according to claim 1, wherein  
said ancillary information comprises program specific  
information for conveying an electronic program guide from said first  
source, and wherein  
15 said multimedia object is associated with said electronic  
program guide.

10. A storage medium containing digital data representing  
video information comprising:

20 packetized program information representing a video  
program; and

ancillary information (205, 210, 215, 220) including  
information describing a multimedia image object associated with an  
image in said packetized program information, said multimedia object  
25 description information comprising,

(a) a location indicator (610) identifying a location of  
said multimedia object for use in acquiring said multimedia object,  
and

(b) a type indicator (605) identifying a multimedia  
30 object type for use in decoding said multimedia object; and



information (215; 825; 840) for associating said multimedia object with an image in said packetized program information.

5           11. A storage medium according to claim 10, wherein  
said ancillary information comprises program specific  
information containing an electronic program guide, and wherein  
said multimedia object is associated with said electronic  
program guide.

10

12. A method for forming program guide information at a  
first source suitable for decoding packetized program information to  
provide data content of a program, comprising the steps of:

forming information describing a multimedia image object  
15 associated with an image in said packetized program information, said  
multimedia object description information comprising,

(a) a location indicator identifying a location of a  
multimedia object for use in acquiring said multimedia object, and

(b) a type indicator identifying a multimedia object  
20 type for use in decoding said multimedia object; and

forming linking information associating said multimedia  
object with an image in said packetized program information; and

incorporating said multimedia object description  
information and said linking information into packetized data for  
25 output to a transmission channel.

13. A method according to claim 12, wherein  
said location indicator identifies a location of said  
multimedia object in one of (a) said packetized program information  
5 from said first source, and (b) information derived from a second  
source different to said first source.

14. A method according to claim 13, wherein  
said location indicator identifies a location of said  
10 multimedia object from said first source using one of (a) an MPEG  
compatible packet Identifier (PID), (b) an MPEG compatible Digital  
Storage Media code.

15. A method according to claim 13, wherein  
15 said location indicator identifies a location of said  
multimedia object derived from said second source using one of (a) an  
Internet URL, (b) an Internet IP address, (c) an Email address, (d) a  
telephone/fax/videophone number.

20 16. A method according to claim 15, wherein  
said multimedia object type comprises at least one of, (a) a  
video segment or still image, (b) an audio segment, (c) text, (d) an  
Internet web page or Internet data, (e) an advertisement, (f) an icon  
for user selection of a service, (g) an animation segment, (h) an Email  
25 message, (i) a user prompting indicator, and (j) a broadcast channel  
identification icon.

17. A method according to claim 12, wherein  
said multimedia object description information further  
includes at least one of, (a) an object start time, (b) an object duration,  
5 (c) an object display mode, (d) an object version number, (e) an object  
format, for use in decoding.

18. A method according to claim 12, wherein  
said linking information associates said multimedia object  
10 with at least one of, (a) an electronic program guide, (b) a video  
program, (c) an audio program and (d) an Internet web page image.

19. A method for decoding packetized program  
information to provide data content of a program, comprising the  
15 steps of:

identifying ancillary information in said packetized  
program information, said ancillary information including information  
describing a multimedia image object associated with an image in said  
packetized program information, said multimedia object description  
20 information comprising,

(a) a location indicator identifying a location of a  
multimedia object for use in acquiring said multimedia object, and

(b) a type indicator identifying a multimedia object  
type for use in decoding said multimedia object; and

25 acquiring and decoding said multimedia object using said  
multimedia object description information; and

formatting said multimedia object for display.

20. A method according to claim 19, including the step of associating said multimedia object with one of (a) a video image, and (b) audio data.

5

21. A method according to claim 20, including the step of forming a composite image for display combining said multimedia object and at least one of, (a) an electronic program guide, (b) a video program, and (c) an Internet web page image.

**AMENDED CLAIMS**

[received by the International Bureau on 30 March 1999 (30.03.99);  
new claims 22-48 added; remaining claims unchanged (15 pages)]

1. Apparatus for decoding packetized program information  
5 from a first source to provide data content of a program, comprising:  
means for identifying (22,60) ancillary information in said  
packetized program information, said ancillary information including  
information describing a multimedia image object associated with an  
image in said packetized program information, said multimedia object  
10 description information comprising,  
(a) a location indicator (610) identifying a location of  
a multimedia object for use in acquiring said multimedia object, and  
(b) a type indicator (605) identifying a multimedia  
object type for use in decoding said multimedia object; and  
15 means for acquiring and decoding (22, 30, 60) said  
multimedia object using said multimedia object description  
information; and  
means for formatting (30, 37, 60) said multimedia object  
for display.  
20
2. Apparatus according to claim 1, wherein  
said location indicator identifies a location of said  
multimedia object in one of (a) said packetized program information  
from said first source, and (b) information derived from a second  
25 source different to said first source.

3. Apparatus according to claim 2, wherein

said location indicator identifies a location of said multimedia object derived from said first source using one of (a) an MPEG compatible packet Identifier (PID), (b) an MPEG compatible Digital Storage Media code.

4. Apparatus according to claim 2, wherein

said location indicator identifies a location of said multimedia object derived from said second source using one of (a) an Internet URL, (b) an Internet IP address, (c) an Email address, (d) a telephone/fax/videophone number.

5. Apparatus according to claim 4, wherein

said means for acquiring said multimedia object includes establishing bi-directional communication with said second source using said location indicator, and said bi-directional communication path is different to the communication path between said decoding apparatus and said first source.

6. Apparatus according to claim 1, wherein

said multimedia object type comprises at least one of, (a) a video segment or still image, (b) an audio segment, (c) text, (d) an Internet web page or Internet data, (e) an advertisement, (f) an icon for user selection of a service, (g) an animation segment, (h) an Email message, (i) a user prompting indicator, and (j) a broadcast channel identification icon.

7. Apparatus according to claim 1, wherein  
said multimedia object description information further  
includes at least one of, (a) an object start time, (b) an object duration,  
5 (c) an object display mode, (d) an object version number, (e) an object  
format, for use in decoding.

8. Apparatus according to claim 1, wherein  
said formatting means includes means for associating said  
10 multimedia object with one of (a) a video image, and (b) audio data,  
and

said formatting means forms a composite image for  
display combining said multimedia object and at least one of, (a) an  
electronic program guide, (b) a video program, and (c) an Internet  
15 web page image.

9. Apparatus according to claim 1, wherein  
said ancillary information comprises program specific  
information for conveying an electronic program guide from said first  
20 source, and wherein

said multimedia object is associated with said electronic  
program guide.

10. A storage medium containing digital data representing  
25 video information comprising:

packetized program information representing a video  
program; and

ancillary information (205, 210, 215, 220) including  
information describing a multimedia image object associated with an

image in said packetized program information, said multimedia object description information comprising,

(a) a location indicator (610) identifying a location of said multimedia object for use in acquiring said multimedia object,  
5 and

(b) a type indicator (605) identifying a multimedia object type for use in decoding said multimedia object; and

information (215; 825; 840) for associating said multimedia object with an image in said packetized program  
10 information.

11. A storage medium according to claim 10, wherein said ancillary information comprises program specific information containing an electronic program guide, and wherein  
15 said multimedia object is associated with said electronic program guide.

12. A method for forming program guide information at a first source suitable for decoding packetized program information to  
20 provide data content of a program, comprising the steps of:

forming information describing a multimedia image object associated with an image in said packetized program information, said multimedia object description information comprising,

(a) a location indicator identifying a location of a  
25 multimedia object for use in acquiring said multimedia object, and

(b) a type indicator identifying a multimedia object type for use in decoding said multimedia object; and

forming linking information associating said multimedia object with an image in said packetized program information; and



incorporating said multimedia object description information and said linking information into packetized data for output to a transmission channel.

5           13. A method according to claim 12, wherein  
said location indicator identifies a location of said multimedia object in one of (a) said packetized program information from said first source, and (b) information derived from a second source different to said first source.

10           14. A method according to claim 13, wherein  
said location indicator identifies a location of said multimedia object from said first source using one of (a) an MPEG compatible packet Identifier (PID), (b) an MPEG compatible Digital  
15 Storage Media code.

          15. A method according to claim 13, wherein  
said location indicator identifies a location of said multimedia object derived from said second source using one of (a) an  
20 Internet URL, (b) an Internet IP address, (c) an Email address, (d) a telephone/fax/videophone number.

          16. A method according to claim 15, wherein  
said multimedia object type comprises at least one of, (a) a  
25 video segment or still image, (b) an audio segment, (c) text, (d) an Internet web page or Internet data, (e) an advertisement, (f) an icon for user selection of a service, (g) an animation segment, (h) an Email message, (i) a user prompting indicator, and (j) a broadcast channel identification icon.

17. A method according to claim 12, wherein  
said multimedia object description information further  
includes at least one of, (a) an object start time, (b) an object duration,  
5 (c) an object display mode, (d) an object version number, (e) an object  
format, for use in decoding.

18. A method according to claim 12, wherein  
said linking information associates said multimedia object  
10 with at least one of, (a) an electronic program guide, (b) a video  
program, (c) an audio program and (d) an Internet web page image.

19. A method for decoding packetized program  
information to provide data content of a program, comprising the  
15 steps of:

identifying ancillary information in said packetized  
program information, said ancillary information including information  
describing a multimedia image object associated with an image in said  
packetized program information, said multimedia object description  
20 information comprising,

(a) a location indicator identifying a location of a  
multimedia object for use in acquiring said multimedia object, and

(b) a type indicator identifying a multimedia object  
type for use in decoding said multimedia object; and

25 acquiring and decoding said multimedia object using said  
multimedia object description information; and  
formatting said multimedia object for display.

20. A method according to claim 19, including the step of associating said multimedia object with one of (a) a video image, and (b) audio data.

5

21. A method according to claim 20, including the step of forming a composite image for display combining said multimedia object and at least one of, (a) an electronic program guide, (b) a video program, and (c) an Internet web page image.

10

22. Apparatus for decoding packetized program information from a first source to provide data content of a program, comprising:

15 means for identifying ancillary information in said packetized program information, said ancillary information including information describing a method associated with an image object in said packetized program information, said method description information comprising,

(a) information enabling identification of a method,

20 and

(b) information for initiating activation of said method upon a predetermined event; and

means for acquiring and decoding said method using said method description information; and

25 means for initiating activation of said method upon said predetermined event using said method description information.

23. Apparatus according to claim 22, wherein  
said method comprises software for performing at least  
one of the following functions, (a) altering user interface display  
5 controls, (b) generating an image window within an encompassing  
image (c) generating an HTML or SGML document (d) generating a  
menu of selectable items (e) generating an icon representing a user  
selectable item for display, (f) generating an image window for  
initiating Internet access, (g) generating an image window supporting  
10 an electronic commerce transaction, and (h) dialing a telephone  
number.

24. Apparatus according to claim 23, wherein altering user  
interface display controls comprises modifying at least one of  
15 (a) keyboard/mouse button response characteristics, (b)  
display video characteristics, and (c) audio characteristics.

25. Apparatus according to claim 22, wherein  
said method comprises software for at least one of,  
20 (a) providing descriptive text for said image object,  
and  
(b) providing at least one user selectable control  
item associated with said image object.

26. Apparatus according to claim 22, wherein  
said information for initiating activation of said method  
upon a predetermined event comprises information for at least one of,  
5 (a) activating said method in response to user selection of a command  
or displayed menu item, (b) activating said method in response to a  
scheduled event, (c) activating said method in sequence following  
completion of a particular function, and (d) activating said method  
substantially immediately said method is processed and ready for  
10 activation.

27. Apparatus according to claim 26, wherein  
said information for initiating activation of said method  
upon a scheduled event comprises a start time indication.

15 28. Apparatus according to claim 27, wherein  
said start time indication is associated with a specific  
video program and is derived from electronic program guide  
information.

20 29. Apparatus according to claim 27, wherein  
said information for initiating activation of said method  
further includes a duration.

25 30. Apparatus according to claim 22, wherein  
said ancillary information includes electronic program  
guide information from said first source.

31. Apparatus according to claim 27, wherein  
said ancillary information further includes information for  
acquiring said method from said first source comprising,

5 a data identifier for identifying a location of said method  
conveyed within said packetized program information from said first  
source.

32. Apparatus according to claim 22, wherein  
10 said ancillary information further includes acquisition  
information for use in acquiring said method from a second source  
different to said first source, and

said acquisition information includes one of (a) an  
Internet URL, (b) an Internet IP address, (c) an Email address, and (d)  
15 a telephone/fax/videophone number.

33. Apparatus according to claim 32, wherein  
said means for acquiring said method includes  
establishing bi-directional communication with said second source  
20 using said acquisition information, and said bi-directional  
communication path is different to the communication path between  
said decoding apparatus and said first source.

34. Apparatus according to claim 22, including  
25 formatting means for forming a composite image for  
display combining an image produced using said method and at least  
one of, (a) an electronic program guide, (b) a video program, and (c)  
an Internet web page image.

35. A storage medium containing digital data representing video information comprising:

packetized program information representing a video program; and

5 ancillary information including information describing a method associated with an image object in said packetized program information, said method description information comprising,

(a) information enabling identification of a method, and

10 (b) information for initiating activation of said method upon a predetermined event; and

information for associating said method with an image object in said packetized program information.

15 36. A storage medium according to claim 35, wherein said ancillary information includes electronic program guide information, and wherein

said method is associated with said electronic program guide.

20

37. A method for forming program guide information at a first source suitable for decoding packetized program information to provide data content of a program, comprising the steps of:

25 forming information describing a method associated with one or more images in said packetized program information, said method description information comprising,

(a) information enabling identification of a method, and

30 (b) information for initiating activation of said method upon a predetermined event; and

forming linking information associating said method with an image in said packetized program information; and

incorporating said method description information and said linking information into packetized data for output to a transmission channel.

38. A method according to claim 37, wherein said method identification information identifies a location of said method in said packetized program information from said first source.

39. A method according to claim 37, wherein said method description information includes data for acquiring said method from a second source different to said first source using one of (a) an Internet URL, (b) an Internet IP address, (c) an Email address, (d) a telephone/fax/videophone number.

40. A method according to claim 37, wherein said linking information associates said method with at least one of, (a) an electronic program guide, (b) a video program, (c) an audio program and (d) an Internet web page image.

41. A method for processing packetized program information to provide data content of a program, comprising the steps of:

identifying ancillary information in said packetized program information, said ancillary information including information describing a method associated with one or more images in said packetized program information, said method description information comprising,



(a) information enabling identification of a method, and

(b) information for initiating activation of said method upon a predetermined event; and

5 acquiring and decoding said method using said method description information; and

initiating activation of said method upon said predetermined event using said method description information.

10 42. A method according to claim 41, wherein said acquiring step comprises

acquiring said method from a second source different to said first source, using one of (a) an Internet URL, (b) an Internet IP address, (c) an Email address, and (d) a telephone/fax/videophone  
15 number.

43. A method according to claim 41, wherein said initiating activation step comprises

initiating activation of said method by at least one of, (a)  
20 activating said method in response to user selection of a command or displayed menu item, (b) activating said method in response to a scheduled event, (c) activating said method in sequence following completion of a particular function, and (d) activating said method substantially immediately said method is processed and ready for  
25 activation.

44. A method for processing packetized program information from a first source to provide data content of a program, comprising the steps of:

5 identifying ancillary information in said packetized program information, said ancillary information including,

(a) a first identifier for identifying a location of data representing a multimedia object, and

10 (b) a second identifier for identifying a location of data representing program guide information, and

(c) a third identifier for identifying a location of data representing a video program in said packetized program information, and

15 acquiring and decoding said multimedia object, said program guide information and said video program data using said ancillary information; and

formatting acquired data for display.

45. A method according to claim 44, wherein said ancillary  
20 information further includes

(d) a fourth identifier for identifying a location of data representing a method.

46. A method according to claim 44, wherein said said  
25 first, second and third identifiers identify a location of said multimedia object in either one of (a) said packetized program information from said first source, and (b) information derived from a second source different to said first source.

47. A method according to claim 46, wherein said  
information is derived from said second source different  
to said first source using one of (a) an Internet URL, (b) an Internet IP  
address, (c) an Email address, (d) a telephone/fax/videophone  
5 number.

48. A method according to claim 44, wherein said  
formatting step includes the steps of  
associating said multimedia object with one of (a) a video  
10 image, and (b) audio data, and

forming a composite image for display combining said  
multimedia object and at least one of, (a) an electronic program guide,  
(b) a video program, and (c) an Internet web page image.

1/13





FIG. 1

2/13

FIGURE 2



3/13

SYNTAX	BITS	FORMAT
MGT_message () {		
reserved	2	'11'
life_time	22	uimbsf
current_time	40	uimbsf
Num_bytes_AGDT	16	uimbsf
}		

FIG. 3

SYNTAX	BITS	FORMAT
AGDT_message () {		
reserved	3	'111'
CCT_version	5	uimbsf
reserved	4	'1111'
EPG_descriptors_length	12	uimbsf
for (i=0;i<N;i++) {		
descriptor ()	var	
}		
num_bytes_CCT	16	uimbsf
number_of_networks	8	uimbsf
for (i = 0 ; i < number_of_networks; i++){		
reserved	3	'111'
NIT_version	5	uimbsf
num_bytes_NIT[i]	16	uimbsf
reserved	4	'1111'
network_descriptors_length	12	uimbsf
for (i=0;i<N;i++){		
descriptor ()		
}		
}		
program_guide_map ()	var	
}		

FIG. 4

4/13

	SYNTAX	BITS	FORMAT
	program_guide_map () {		
	number_channel_groupings	4	uimsbf
	SPG_map_descriptors_length	12	uimsbf
505	for (i=0; i<N; i++) {		
	descriptor ()	var	
	}		
	for (i = 0; i<number_channel_groupings+1; i++) {		
	reserved	4	'1111'
	start_channel(i)	12	uimsbf
	}		
	number_guides	8	uimsbf
	reserved	4	'1111'
	program_guide_map_size	12	uimsbf
510	for (i = 0; i< number_guides+1; i++) SPG_map(i) {		
	next	8	uimsbf
	previous	8	uimsbf
	left_column_time	40	bslbf
	width_in_minutes	16	uimsbf
	reserved	4	'1111'
	SPG_descriptors_length	12	uimsbf
515	for (i=0; i<N; i++) {		
	descriptor ()	var	
	}		
520	Nbytes_list_SPG (i) {		
	for (j = 0; j< number_channel_groupings+1; j++)		
	reserved	4	'1111'
	group[j]_descriptors_length	12	uimsbf
525	for (l=0; l<N; l++) {		
	descriptor ()	var	
	}		
	Num_bytes_SPG[i]_CIT[j]	16	uimsbf
	Num_bytes_SPG[i]_ECIT[j]	16	uimsbf
	Num_bytes_SPG[i]_EIT[j]	16	uimsbf
	Num_bytes_SPG[i]_EEIT[j]	16	uimsbf
	}		
	SPG_name_length	8	uimsbf
	for(i=0; i< SPG_name_length; i++)		
	SPG_name(i)	8	ISO-639
	}		
	}		

FIG. 5

5/13

	SYNTAX	BITS	FORMAT
	multimedia object descriptor() {		
	descriptor_tag	8	0x5F
	descriptor_length	8	uimsbf
605	object_type	8	uimsbf
	if (object_type = 0xFF) {		
	extended_object_type	16	uimsbf
	}		
610	address_descriptor		
	object_format	8	uimsbf
	object_version_number	7	uimsbf
	display_mode	1	0/1
	object_start_time	40	uimsbf
	object_duration_format	2	uimsbf
	object_duration	14	uimsbf
	object_frame_size	32	uimsbf
	}		

FIG. 6



6/13

ELEMENT	DEFINITION
descriptor_tag	SET TO 0x5F TO IDENTIFY THE DESCRIPTOR AS AN OBJECT DESCRIPTOR.
descriptor_length	DESCRIPTOR LENGTH IN BYTES FOLLOWING THIS FIELD.
object_type and extended_object_type	SPECIFIES OBJECT TYPE.
address_descriptor	OBJECT ADDRESS.
object_format	OBJECT FORMAT.
object_version_number	SPECIFIES THE CURRENT VERSION OF THE OBJECT. AN APPLICATION, FOR EXAMPLE CAN USE THIS FIELD TO DETERMINE WHETHER IT SHOULD RELOAD THE OBJECT THAT IS ALREADY PRESENT IN THE BOX.
display mode	THIS FIELD CAN EITHER BE "ON-DEMAND"(0) OR "IMMEDIATE"(1). WHEN AN "IMMEDIATE" OBJECT BECOMES "ALIVE" AS DETERMINED BY THE object_start_time, WE SHOULD IMMEDIATELY NOTIFY THE USER ABOUT THE AVAILABILITY. E.g.: AN OBJECT ASSOCIATED WITH A COMMERCIAL THAT IS BEING Aired. THE AVAILABILITY OF AN "ON DEMAND" OBJECT IS NOTIFIED TO THE USER ONLY WHEN THE USER WANTS TO SEE THE AVAILABLE OBJECTS LIST.
object_start_time	SPECIFIES THE TIME AT WHICH THE OBJECT BECOMES "ALIVE".
object_duration_format	THE OBJECT IS AVAILABLE FOR THE USER STARTING FROM THIS TIME.
object_duration	IF THE VALUE IS 1/2/3/4 THEN THE object_duration IS IN SECONDS, MINUTES, HOURS, OR DAYS RESPECTIVELY.
object_frame_size	SPECIFIES THE TIME AT WHICH THE OBJECT EXPIRES.
	OBJECT FRAME SIZE IN BYTES. Object_frame_consists_of_the_object_header_and_the_actual_object.

FIG. 7

7/13




FIG. 8

ELEMENT	DEFINITION
rating_descriptor	THE rating_descriptor SPECIFIES THE PARENTAL RATING FOR THE OBJECT.
ca_descriptor	THE ca_descriptor SPECIFIES THE CONDITIONAL ACCESS SYSTEM FOR THE OBJECT.
telephone_descriptor	THE telephone_descriptor SPECIFIES THE TELEPHONE NUMBER AND RELATED INFORMATION ASSOCIATED WITH THE OBJECT.
method_descriptor	THE method_descriptors ASSOCIATED WITH AN OBJECT DESCRIBE THE METHODS AND THE EVENTS THAT WILL TRIGGER THEM.
linkage_descriptor	THE linkage_descriptor LINKS OTHER DESCRIPTORS TO THE CURRENT OBJECT DESCRIPTOR.
attribute_descriptor	THE attribute_descriptor SHALL BE USED TO SPECIFY THE SPECIAL ATTRIBUTES OF THE CURRENT OBJECT.
just_in_time_object descriptor	THIS DESCRIPTOR IS USED TO INDICATE THE ADDRESS OF THE MODs AND OBJECTS THAT ARE NOT KNOWN IN ADVANCE.
content_descriptor	THIS DESCRIPTOR IS USED TO SPECIFY THE OBJECTS PROFILE VALUES FOR TARGETTED COMMERCIALS.

FIG. 9

8/13

SYNTAX	BITS	FORMAT
remote_http_object_address_descriptor() {		
descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
URL_length	8	uimsbf
for (i = 0; i < URL_length; i++) {		
905 — URL(i)	8	ISO-639
}		
}		

FIG. 10

SYNTAX	BITS	FORMAT
DSM-CC_object_address_descriptor() {		
descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
910 — DSM-CC_association_tag	16	uimsbf
}		

FIG. 11

SYNTAX	BITS	FORMAT
MPEG_PSI_PS_address_descriptor() {		
descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
default_primary_location_bit	1	0/1
if (default_primary_location_bit == 0) {		
915 — network_id	8	uimsbf
920 — transport_channel_id	8	uimsbf
}		
default_secondary_location_bit	1	0/1
if (default_secondary_location_bit == 0) {		
925 — PID	13	uimsbf
930 — table_id	8	uimsbf
table_id_extension	16	uimsbf
}		
}		

FIG. 12

9/13

SYNTAX	BITS	FORMAT
descriptor_tag	8	uimsbf
descriptor_length	8	uimsbf
950 number_elements	8	uimsbf
for (i=0;i<number_elements;i++) {		
reserved	3	'111'
size_flag	1	uimsbf
955 element_identifier	12	uimsbf
if (transport == broadcast) {		
960 transport_channel_ID	8	uimsbf
reserved	3	'111'
965 PID	13	uimsbf
}		
else if (transport == file based) {		
file_name_length	8	uimsbf
for (i=0;i<address_length;i++)		
970 file_char	8	ISO-639
}		
if (size_flag == 1) {		
element_size	32	uimsbf
}		

FIG. 13

element_identifier	description
0x000	user private
0x001	Private Information Parcel (PIP)
0x002	Extended Text Table (ETT)
0x003	Network Information Table (NIT)
0x004	Special Program Guide (SPG)
0x005	Channel Information Table (CIT)
0x006	Extended Channel Information Table (ECIT)
0x007	Event Information Table (EIT)
0x008	Extended Event Information Table (EEIT)

FIG. 14

10/13

	SYNTAX	BITS	FORMAT
	location_descriptor () {		
980	descriptor_tag	8	uimbsf
	descriptor_length	8	uimbsf
	number_PIDs	8	uimbsf
	reserved	7	'1111111'
	implicit_flag	1	bslbf
985	if (implicit_flag == 0x00){		
987	for (i=1;i<number_PIDs;i++){		
	reserved	3	'111'
990	PID[i]	13	uimbsf
	SType[i]	8	uimbsf
	}		
	} else {		
	reserved	3	'111'
993	base_PID	13	uimbsf
	}		
	}		

FIG. 15

11/13

	SYNTAX	BITS	FORMAT
350	location_descriptor () {		
	descriptor_tag	8	uimsbf
	descriptor_length	8	uimsbf
	number_SCIDs	8	uimsbf
	reserved	6	'111111'
	Z_bit	1	bslbf
	implicit_flag	1	bslbf
353	if (implicit_flag == 0x00){		
	for (i=1;i<number_SCIDs;i++){		
	if (Z_bit==0)		
355	SCID[i]	8	uimsbf
	else{		
	reserved	4	'1111'
357	SCID[i]	12	uimsbf
	} SType[i]	8	uimsbf
	} else {		
	if (Z_bit==0)		
360	base_SCID	8	uimsbf
	else{		
	reserved	4	'1111'
363	base_SCID	12	uimsbf
	}		
	}		
	}		

FIG. 16





FIG. 17



**FIG. 18**



# INTERNATIONAL SEARCH REPORT

In national Application No

PCT/US 98/21556

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H04N7/24 H04N5/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	EP 0 848 553 A (NEXTLEVEL SYSTEMS INC) 17 June 1998 see the whole document ---	1-21
P,X	US 5 818 935 A (MAA CHIA-YIU) 6 October 1998 see the whole document ---	1-21
P,X	EP 0 805 590 A (MATSUSHITA ELECTRIC IND CO LTD) 5 November 1997 see the whole document ---	1,12
P,X	WO 97 43838 A (NOKIA OY AB ;SALOMAEKI ARI (FI)) 20 November 1997 see abstract --- -/-	1,12



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 February 1999

Date of mailing of the international search report

16/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Giannotti, P

# INTERNATIONAL SEARCH REPORT

In. ational Application No

PCT/US 98/21556

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	TEN KATE W. ET AL.: "trigg&link: a new dimension in television program making" MULTIMEDIA APPLICATIONS, SERVICES AND TECHNIQUES - ECMAS'T'97, 21 - 23 May 1997, pages 51-65, XP002094655 Milan, Italy see page 52, line 11 - page 53, line 14 see page 57, line 1 - page 58, line 16 see figure 2	1-21
Y	ETS 300 468: "digital broadcasting systems for television, sound and data services; specification for service information (SI) in digital broadcasting (DVB) systems" EUROPEAN TELECOMMUNICATION STANDARD, ROPEAN TELECOMMUNICATIONS STANDARDS INSTITUTE, EU, October 1995, XP002079535 see section 6.2.8 on page 38 see section 6.2.13 on page 44 see 6.2.14 on page 45	1-21
A	US 5 515 106 A (BRIDGEWATER KEVIN E ET AL) 7 May 1996 see the whole document	1-21
A	WO 96 42144 A (NOKIA OY AB ;SALOMAEKI ARI (FI)) 27 December 1996 see abstract	1-21
A	G.ALBERICO AND M. COMINETTI: "Satellite Interactive Multimedia: a new opportunity for broadcasters" INTERNATIONAL BROADCASTING CONVENTION, 12 - 16 September 1997, pages 18-23, XP002094656 London, UK, IEE, UK	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

1. national Application No

PCT/US 98/21556

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0848553 A	17-06-1998	CA 2223095 A CN 1195938 A JP 10247945 A	10-06-1998 14-10-1998 14-09-1998
US 5818935 A	06-10-1998	NONE	
EP 0805590 A	05-11-1997	JP 9298721 A CN 1173098 A	18-11-1997 11-02-1998
WO 9743838 A	20-11-1997	FI 961980 A AU 2702297 A	10-11-1997 05-12-1997
US 5515106 A	07-05-1996	AU 695654 B AU 1521795 A AU 680340 B AU 1598195 A AU 691209 B AU 8157294 A BR 9500013 A BR 9506446 A BR 9506447 A CA 2138603 A CA 2180111 A CA 2180112 A CN 1115950 A CN 1141707 A CN 1141708 A EP 0662771 A EP 0738449 A EP 0738450 A EP 0838958 A FI 962756 A FI 962757 A JP 8070451 A JP 9507359 T JP 9507361 T WO 9519091 A WO 9519092 A US 5642153 A	20-08-1998 01-08-1995 24-07-1997 01-08-1995 14-05-1998 13-07-1995 26-09-1995 02-09-1997 02-09-1997 06-07-1995 13-07-1995 13-07-1995 31-01-1996 29-01-1997 29-01-1997 12-07-1995 23-10-1996 23-10-1996 29-04-1998 30-07-1996 30-07-1996 12-03-1996 22-07-1997 22-07-1997 13-07-1995 13-07-1995 24-06-1997
WO 9642144 A	27-12-1996	FI 98175 B AU 6127696 A EP 0872053 A	15-01-1997 09-01-1997 21-10-1998

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

This Page Blank (uspto)